

Walk-Through Metal Detector

The STC-1104 is a popular walk-through metal detector because it provides maximum throughput with exceptional multidimensional scanning. The STC-1104 meets the demanding needs of security professionals worldwide who trust its ability to maintain patron flow rate with minimal alarms.



FEATURES

- 5.7 inch LCD screen with Infrared remoter controller
- Adopt advanced digital signal processing control replaced traditional analog signal control, better stability.
- Friendly windows interface, both Chinese and English program, easy to operate.
- Program Self-diagnostic when power on , automatically checking left and right door panel, LED light and choose the best working frequency.
- Automatically count passengers and alarm times, keep alarm records for inquiry (up to 20000 records)
- Detecting Zones: 6 detecting loops, can extend to 12,18zones by separate left, right, middle side detection to pinpoint detection (As follow picture)
- Sensitivity adjustable: Each zone has 255 degree sensitivity level, three patterns: High, middle, Low for different requirements. Preset the metal size, weight, volume, location to exclude the coin, key, belt..
- Sound Alarm: 1-25s alarm time, 255 different sound volume and 12 tones for choose
- LED light alarm: LED bar graph on left and right door frame, visible alarm simultaneously to ascertain the layout of metal articles
- Lock and Password protection, only the authorized person can operate.
- Anti- interference function , using advanced interactive transmitting and receiving to avoid interference, frequency range from 4K-8K to avoid frequency interference
- 6 preset programs for security application versatility
- 4 hours Battery backup , the uninterruptible power protection system secure the parameters when power off.
- PVC material and Control unit on the top , waterproof, moisture-proof and cooler.
- Integrated and modularized circuit design lead to simple installation and more convenient after services.
- Adjustable Passing speed: up to 100 persons/min
- Background light: 0-99 seconds for choose
- Battery Backup not less than 4 hours.
- Calendar function: real time display year, month, date, hour, minute, second
- Harmless to heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc.
- Network support: (For Option)

Product Detail

Electric current: AC85V~264V/50-60HZ
Power: <20W, low consume, low radiation
Gross weight: 70KG
Workplace environment: -20°C ~ +50°C
Standard: GB15210-2003, CE

Standard External size:
2230mm(H)X835mm(W)X580mm(D)
Standard Internal size:
1990mm(H)X700mm(W)X500mm(D)